

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***
Supersedes Version 2 .00***

Revision Date 18-May-2015
Issuing date 26-May-2015

SECTION 1: Identification

1.1. Product identifier

Identification of the
substance/preparation

Di-(2-ethylhexyl) amine

CAS-No 106-20-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance /
Preparation Intermediate

1.3. Details of the supplier of the safety data sheet

Supplier **OXEA Corporation**
1505 West LBJ Freeway, Suite 400
Dallas, TX 75234
USA
Phone: +1 972 481 2700

Product Information Product Stewardship
FAX: +49 (0)208 693 2053
email: psq@oxea-chemicals.com

1.4. Emergency telephone number

Emergency telephone number in USA, call 800 424 9300
outside USA, call 703 527 3887, collect calls accepted
available 24/7***

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This substance is classified in accordance with paragraph (d) of §1910.1200 (GHS-US classification).***

Acute oral toxicity Category 4, H302***
Acute dermal toxicity Category 3, H311***
Acute inhalation toxicity Category 3, H331***
Skin corrosion/irritation Category 1B, H314***
Serious eye damage/eye irritation Category 1, H318***
Environmental hazard Aquatic Acute 2; H401; Aquatic Chronic 1; H410***

OSHA Specified Hazards Not applicable.

Emergency telephone number in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
1 / 13 USA (A-US)

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

2.2. Label elements

Labeling according to §1910.1200 (GHS-US labeling).***

Hazard symbol(s)



Signal word

Danger***

Hazard statements

H302: Harmful if swallowed.
H311 + H331: Toxic in contact with skin or if inhaled
H314: Causes severe skin burns and eye damage.
H401: Toxic to aquatic life
H410: Very toxic to aquatic life with long lasting effects.***

Precautionary statements

Prevention

P280: Wear protective gloves/protective clothing.
P260: Do not breathe gas/mist/vapours.
P271: Use only outdoors or in a well-ventilated area.
P264: Wash hands thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.***

Response

P301 + P330 + P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P321: Specific treatment: IF ON SKIN: Wash off with 3% acetic acid followed by large amounts of plain water for at least 5 min as a final step.
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P361: Take off immediately all contaminated clothing and wash it before reuse.
P310: Immediately call a POISON CENTER/doctor.***

Storage

P403 + P233: Store in a well-ventilated place. Keep container tightly closed.
P405: Store locked up.***

Disposal

P501: Dispose of contents/container in accordance with local regulation.***

2.3. Other hazards

Emergency telephone number
2 / 13

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

Components of the product may be absorbed into the body through the skin
Vapour/air-mixtures are explosive at intense warming***

SECTION 3: Composition/information on ingredients

3.1. Substances

Component	CAS-No	Concentration (%)
Bis-(2-ethylhexyl)-amine	106-20-7	> 99,0

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Keep at rest. Aerate with fresh air. Call a physician immediately. Symptoms of poisoning may develop many hours after exposure.

Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.

Skin

Wash off with 3% acetic acid followed by large amounts of plain water for at least 5 min as a final step. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.

Ingestion

Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Main symptoms

shortness of breath, convulsions, cough, hypertensive effect, nausea, vomiting, circulatory collapse, discomfort.

Special hazard

Stomach perforation, Lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

General advice

Remove contaminated, soaked clothing immediately and dispose of safely. First aider needs to protect himself.

Treat as an alkaline substance (similar to ammonia). If ingested, irrigate the stomach. Treat skin and mucous membranes with antihistamine and corticoids. In case of lung irritation, first treatment with cortisone spray. Symptoms may be delayed. Later control for pneumonia and lung oedema.

SECTION 5: Firefighting measures

Emergency telephone number
3 / 13

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

5.1. Extinguishing media

Suitable extinguishing media

alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water spray

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Under conditions giving incomplete combustion, hazardous gases produced may consist of:

carbon monoxide (CO)

carbon dioxide (CO₂)

nitrogen oxides (NO_x)

Combustion gases of organic materials must in principle be graded as inhalation poisons

Vapours are heavier than air and may spread along floors

Vapour/air-mixtures are explosive at intense warming

5.3. Advice for firefighters

Special protective equipment for firefighters

Fire fighter protection should include a self-contained breathing apparatus (NIOSH-approved or EN 133) and full fire-fighting turn out gear.

Precautions for firefighting

Cool containers / tanks with water spray. Dike and collect water used to fight fire. Water run-off and vapor cloud may be corrosive. Water run-off can cause environmental damage. Keep people away from and upwind of fire. Do not allow run-off from fire fighting to enter drains or water courses.***

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation, especially in confined areas. Keep away from heat and sources of ignition.

For emergency responders: Personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage. Do not discharge product into the aquatic environment without pretreatment (biological treatment plant). Water runoff can cause environmental damage.

6.3. Methods and material for containment and cleaning up

Methods for containment

Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

Methods for cleaning up

Soak up with inert absorbent material. DO NOT use combustible materials such as sawdust. Keep in suitable, closed containers for disposal. If liquid has been spilt in large quantities clean up promptly by scoop or vacuum. Dispose of in accordance with local regulations. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

6.4. Reference to other sections

For personal protective equipment see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with skin, eyes and clothing. Do not use compressed air for filling, discharging or handling. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms. Refill and handle product only in closed system.

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Advice on the protection of the environment

See Section 8: Environmental exposure controls.

Incompatible products

strong acids
oxidizing agents

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). In case of fire, emergency cooling with water spray should be available. Ground and bond containers when transferring material. Vapour/air-mixtures are explosive at intense warming.

Technical measures/Storage conditions

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care. Handle under nitrogen, protect from moisture. Keep at temperatures between -1 and 38 °C (30 and 100 °F).

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits United States of America

No exposure limits established regarding ACGIH, OSHA Z-1 and OSHA Z-2.***

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

8.2. Exposure controls

Appropriate Engineering controls

General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.

Individual protection measures, such as personal protective equipment

General industrial hygiene practice

Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Ensure that eyewash stations and safety showers are close to the workstation location.

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Eye protection

Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.

Hand protection

Wear protective gloves. Recommendations are listed below. Other protective material may be used, depending on the situation, if adequate degradation and permeation data is available. If other chemicals are used in conjunction with this chemical, material selection should be based on protection for all chemicals present.

Suitable material	Viton
Evaluation	according to EN 374: level 6
Glove thickness	approx 0,5 mm
Break through time	> 480 min

Suitable material	polyvinylchloride
Evaluation	Information derived from practical experience
Glove thickness	approx 0,8 mm

Skin and body protection

Impervious clothing. Wear face-shield and protective suit for abnormal processing problems.

Respiratory protection

Respirator with filter for ammonia vapour and ammonia derivatives (K Filter). Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Equipment should conform to NIOSH.

Environmental exposure controls

Use product only in closed system. If leakage can not be prevented, the substance needs to be suck off at the emersion point, if possible without danger. If recycling is not practicable, dispose of in compliance with local regulations. Inform the responsible authorities in case of leakage into the atmosphere, or of entry into waterways, soil or drains.

SECTION 9: Physical and chemical properties

Emergency telephone number
6 / 13

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision

3 .00***

9.1. Information on basic physical and chemical properties

Appearance liquid
Colour colourless
Odour amine-like
Odour threshold No data available
pH 9,0 (0,01 g/l in water @ 25 °C (77 °F)) DIN 19268
Melting point/range - 128 °F (- 89 °C)
Boiling point/range 531 °F (277 °C) @ 1 atm (101,3 kPa)
Flash point 266 °F (130 °C)
Method DIN EN ISO 2719
Evaporation rate No data available
Flammability (solid, gas) Does not apply, the substance is a liquid
Lower explosion limit 0,6 Vol %
Upper explosion limit 3,7 Vol %

Vapour pressure ***
Values Values Values @ °C @ °F Method
[hPa] [kPa] [atm]
0,013 0,001 < 0,001 20 68
0,06 0,006 < 0,001 50 122

Vapour density No data available

Relative density ***
Values @ °C @ °F Method
0,8040 20 68 DIN 51757

Solubility No data available
Water solubility 14 mg/l @ 68 °F (20 °C) OECD 105
log Pow 7,3 (measured) OECD 117
Autoignition temperature 473 °F (245 °C)
Method DIN 51794
Decomposition temperature No data available
Viscosity 3,7 mPa*s @ 68 °F (20 °C)
Method ASTM D445, dynamic

9.2. Other information

Molecular weight 241,46
Molecular formula C16 H35 N
Oxidizing properties Does not apply, substance is not oxidising. There are no chemical groups associated with oxidizing properties
Refractive Index 1,442 @ 68 °F (20 °C)
Explosive properties Does not apply, substance is not explosive. There are no chemical groups associated with explosive properties
Surface tension 48,0 mN/m (0,0125 g/l @ 20°C), OECD 115

SECTION 10: Stability and reactivity

10.1. Reactivity

Emergency telephone number
7 / 13

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

The reactivity of the product corresponds to the typical reactivity shown by the substance group as described in any text book on organic chemistry.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Vapour/air-mixtures are explosive at intense warming.

10.4. Conditions to avoid

Avoid contact with heat, sparks, open flame and static discharge. Avoid any source of ignition.

10.5. Incompatible materials

strong acids, oxidizing agents.

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed. If heated to thermal decomposition the following decomposition products may occur depending on the conditions. carbon monoxide (CO). nitrogen oxides (NOx). cyanides. nitric acid. nitriles.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure Ingestion, Inhalation, Skin contact, Eye contact

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

Main symptoms

shortness of breath, convulsions, cough, hypertensive effect, nausea, vomiting, circulatory collapse, discomfort.

Target Organ Systemic Toxicant - Single exposure

respiratory system

Target Organ Systemic Toxicant - Repeated exposure

no data available

Acute toxicity

Bis-(2-ethylhexyl)-amine (106-20-7)

Routes of Exposure	Endpoint	Values	Species	Method
Oral	LD50	1008 mg/kg	rat	
Dermal	LD50	958 mg/kg	rabbit	
Inhalative	LC50	0,91 mg/l (4h)	rat	aerosol

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

Assessment

The available data lead to the classification given in section 2

Emergency telephone number
8 / 13

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

Irritation and corrosion				
Bis-(2-ethylhexyl)-amine (106-20-7)				
Target Organ Effects	Species	Result	Method	
Skin	rabbit	corrosive		
Respiratory tract	rat	irritating	Inhalation Risk Test	
Respiratory tract	mouse	irritating	RD50	

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

Assessment

The available data lead to the classification given in section 2

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

Assessment

Skin sensitization was not tested due to the corrosive properties of the substance

For respiratory sensitization, no data are available

Subacute, subchronic and prolonged toxicity				
Bis-(2-ethylhexyl)-amine (106-20-7)				
Type	Dose	Species	Method	
Subacute toxicity	NOAEL: 75 mg/kg/d	rat	OECD 422	

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

Assessment

Based on available data, the classification criteria are not met for:

STOT RE

Carcinogenicity, Mutagenicity, Reproductive toxicity					
Bis-(2-ethylhexyl)-amine (106-20-7)					
Type	Dose	Species	Evaluation	Method	
Mutagenicity		V79 cells, Chinese hamster	negative	Ames test Micronucleus	
Mutagenicity		V79 cells, Chinese hamster	negative	HPRT	
Reproductive toxicity	NOEL 75 mg/kg/d	rat		OECD 422	
Developmental Toxicity	NOEL 75 mg/kg/d	rat		OECD 422	

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

Evaluation

In vitro tests did not show mutagenic effects

No reprotoxic effects in the absence of maternal toxicity

No cancer study was conducted

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

Aspiration toxicity

no data available

Other adverse effects

Components of the product may be absorbed into the body through the skin.

Note

Handle in accordance with good industrial hygiene and safety practice. Further details on substance data can be found in the registration dossier under the following link: <http://apps.echa.europa.eu/registered/registered-sub.aspx>.

Emergency telephone number in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity			
Bis-(2-ethylhexyl)-amine (106-20-7)			
Species	Exposure time	Dose	Method
Leuciscus idus (Golden orfe)	96h	LC50: > 1,5 - < 2,2 mg/l	DIN 38412, part 15
Daphnia magna (Water flea)	48h	EC50: 2,2 mg/l	79/831/EEC.C2
Desmodesmus subspicatus	72h	EC50: > 1 mg/l (Growth rate)	OECD 201
Activated sludge (bacteriae)	3 h	EC50: 89 mg/l	OECD 209

Long term toxicity				
Bis-(2-ethylhexyl)-amine (106-20-7)				
Type	Species	Dose	Method	
Reproductive toxicity	Daphnia magna (Water flea)	NOEC: 0,069 mg/l (21d)	OECD 211	
Reproductive toxicity	Daphnia magna (Water flea)	LOEC: 0,133 mg/l/21d	OECD 211	
Reproductive toxicity	Earthworm	NOEC: 20 mg/l (56d)	OECD 222	

12.2. Persistence and degradability

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

Biodegradation

40 - 50 % (39 d), activated sludge (domestic), aerobic, OECD 301 B.

12.3. Bioaccumulative potential

log Pow 7,3 (measured) OECD 117

12.4. Mobility in soil

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

No data available

12.5 Other adverse effects

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

No data available

Note

Avoid release to the environment.

Emergency telephone number
10 / 13

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

SECTION 13: Disposal considerations

Product Information

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.

Uncleaned empty packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

D.O.T. (49CFR)

14.1. UN number	*** UN 2922
14.2. UN proper shipping name	*** Corrosive liquids, toxic, n.o.s. (Di-(2-ethylhexyl) amine)
14.3. Transport hazard class(es)	*** 8
Subsidiary Risk	6.1
14.4. Packing group	*** II
14.5. Environmental hazards	***
Marking	Fish and tree
Marine pollutant	yes
14.6. Special precautions for user	***
Emergency Response Guide	154

ICAO/IATA

14.1. UN number	*** UN 2922
14.2. UN proper shipping name	*** Corrosive liquid, toxic, n.o.s. (Di-(2-ethylhexyl) amine)
14.3. Transport hazard class(es)	*** 8
Subsidiary Risk	6.1***
14.4. Packing group	*** II
14.5. Environmental hazards	*** Fish and tree
14.6. Special precautions for user	no data available***

IMDG

14.1. UN number	*** UN 2922
14.2. UN proper shipping name	*** Corrosive liquid, toxic, n.o.s. (Di-(2-ethylhexyl) amine)
14.3. Transport hazard class(es)	*** 8
Subsidiary Risk	6.1***

Emergency telephone number
11 / 13

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

14.4. Packing group	*** II
14.5. Environmental hazards	***
Marking	Fish and tree
Marine pollutant	yes
14.6. Special precautions for user	***
EmS	F-A, S-B
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	not applicable

SECTION 15: Regulatory information

Federal and State Regulations

Components of the product are listed in the quoted regulations. For details please refer to the regulations directly. This list is not exhaustive, please check for other applicable regulations.

Federal Regulations

This product is listed on the TSCA inventory

State Regulations

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

MA RTK List

PA RTK List

International Inventories

Bis-(2-ethylhexyl)-amine, CAS: 106-20-7

AICS (AU)

DSL (CA)

IECSC (CN)

EC-No. 2033724 (EU)

ENCS (2)-133 (JP)

ENCS (2)-176 (JP)

ISHL (2)-133 (JP)

ISHL (2)-176 (JP)

ISHL 2-(10)-66 (JP)

KECI 97-1-120 (KR)

KECI KE-05-0210 (KR)

INSQ (MX)

PICCS (PH)

TSCA (US)

NZIoC (NZ)

TCSI (TW)***

SECTION 16: Other information

Revision Date 18-May-2015

Emergency telephone number 12 / 13 in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted USA (A-US)

SAFETY DATA SHEET



Di-(2-ethylhexyl) amine
10190

Version / Revision 3 .00***

Issuing date 26-May-2015

Hazard Rating Systems

NFPA (National Fire Protection Association)

Health Hazard	3***
Fire Hazard	1
Reactivity	0

HMS (Hazardous Material Information System)

Health Hazard	3
Flammability	1
Physical Hazard	0

Training advice

For effective first-aid, special training / education is needed.

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on Oxea owned data and public sources deemed valid or acceptable. The absence of data elements required by ANSI or Annex II, Regulation 1907/2006/EC indicates, that no data meeting these requirements is available.

Further information for the safety data sheet

Changes against the previous version are marked by ***. Observe national and local legal requirements. For more information, other material safety data sheets or technical data sheets please consult the Oxea homepage (www.oxea-chemicals.com).

Disclaimer

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. Oxea makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

End of Safety Data Sheet