

Ethanol SDA 35A 190 Proof

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade name	Ethanol SDA 35A 190 Proof		
Synonyms	Denatured Alcohol		
Use	Industrial use, Intermediate, Pharmaceutical, Process/Extraction Solvent, Raw material for chemical processes, Raw material for industry, Raw material for pharmaceuticals, Solvent		
Company	Sasol Chemicals (USA) LLC (an affiliate of Sasol Chemicals North America LLC)		
Address	900 Threadneedle Ste 100 Houston TX 77079		
Telephone	CHEMTREC North America Transportation Emergency (24-hr)		(800) 424-9300
	CHEMTREC World Wide		(703) 527-3887
	Other Emergencies (24-hr)		(337) 494-5142
	MSDS and Product Information (8:00am-4:30pm CST)		(281) 588-3491
	Health and Safety Information (7:30am-4:00pm CST)		(281) 588-3492
E-mail address	SasolElectronicSDS@us.sasol.com		

SECTION 2 HAZARDS IDENTIFICATION

GHS Hazards

Flammable liquids	Category 2
Eye irritation	Category 2A

LABEL ELEMENTS**Hazard symbols****Signal word** Danger

Hazard statements H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

Precautionary statements

Prevention P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/ eye protection/ face protection.
P264 Wash skin thoroughly after handling.

Ethanol SDA 35A 190 Proof

Response P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS-No.</u>	<u>Weight percent</u>
Ethanol	64-17-5	96
Ethyl Acetate	141-78-6	4

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.

SECTION 4 FIRST AID MEASURES

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.

Inhalation Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of shortness of breath, give oxygen. Call a physician immediately.

Ingestion If swallowed, call a poison control centre or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.


SECTION 5 FIREFIGHTING MEASURES

FLAMMABLE PROPERTIES

Fire/explosion Flash back possible over considerable distance. NFPA Class IB flammable liquid.

Suitable extinguishing media Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO₂)

Protective equipment and precautions for firefighters Wear self-contained breathing apparatus and protective suit. Keep containers and surroundings cool with water spray.



Ethanol SDA 35A 190 Proof

SECTION 6 ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up Evacuate personnel to safe areas. Remove all sources of ignition. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Do not flush into surface water or sanitary sewer system.

Spill precautions Material can create slippery conditions.

SECTION 7 HANDLING AND STORAGE

Safe handling advice Ensure all equipment is electrically grounded before beginning transfer operations. Keep away from heat and sources of ignition.

Storage/Transport pressure Ambient

Load/Unload temperature Ambient

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES

Ensure adequate ventilation, especially in confined areas.

PERSONAL PROTECTIVE EQUIPMENT

Eyes Wear as appropriate: Goggles, Face-shield

Skin Wear suitable protective clothing, gloves and eye/face protection.

Inhalation Respiratory protection is normally not required except in emergencies or when conditions cause excessive airborne levels of mists or vapors. Use NIOSH approved respiratory protection.

EXPOSURE GUIDELINES

Components	Exposure limit(s)
Ethanol	ACGIH STEL 1,000 ppm OSHA PEL 1,000 ppm 1,900 mg/m ³


Ethyl Acetate	ACGIH TLV (8-hour) 400 ppm 1,400 mg/m ³ OSHA PEL 400 ppm 1,400 mg/m ³
----------------------	--

PEL= Permissible Exposure Limits
TLV= Threshold Limit Value
EL= Excursion Limit

TWA= Time Weighted Average (8 hr.)
STEL= Short Term Exposure Limit (15 min.)
WEEL= Workplace Environmental Exposure Level

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid;

**Ethanol SDA 35A 190 Proof**

Colour	Clear, colorless
Form	liquid
Odour	alcohol-like
Odour Threshold	no data available
Flash point	13 °C, 55.4 °F; TCC (ASTM D56);
Flammability	Upper explosion limit: 20.0 %(V) Lower explosion limit: 4.0 %(V)
Boiling point/boiling range	74 - 80 °C, 165.2 - 176 °F;
Melting point/range	-114.1 °C, -173.4 °F;
Auto-ignition temperature	ca. 400 °C, 752 °F; ASTM D 2155;
Decomposition temperature	no data available
Flammability (solid, gas)	no data available
Vapour pressure	ca. 66.66 hPa @ 20 °C, 68 °F;
Vapour density	no data available
Density	0.814 g/cm ³ @ 20 °C, 68 °F; (200 pf)
Specific gravity	no data available
Water solubility	completely miscible
Viscosity	no data available
pH	no data available
Evaporation rate	no data available
Partition coefficient: n-octanol/water	no data available

SECTION 10 STABILITY AND REACTIVITY


Reactivity	Stable at normal ambient temperature and pressure.
Chemical stability	No decomposition if stored and applied as directed.

Ethanol SDA 35A 190 Proof

Conditions to avoid	Keep away from heat and sources of ignition.
Hazardous decomposition products	Combustion products include carbon dioxide, carbon monoxide and possibly other unidentified organic compounds.
Materials to avoid	Can react with strong oxidizers, inorganic acids, and halogens.
Hazardous polymerisation	None.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute dermal toxicity	LD50 rabbit: > 2,000 mg/kg; OECD Test Guideline 402 Test substance: Ethanol; (literature value)
	LD50 rabbit: > 2,000 mg/kg Test substance: Ethyl Acetate; (literature value)
Acute inhalation toxicity	LC50 mouse (4 hours): > 20 mg/l Test substance: Ethanol; (literature value)
Acute oral toxicity	LD50 rat: 2,000 mg/kg; OECD Test Guideline 401 Test substance: Ethanol; (literature value)
	LD50 rat: > 2,000 mg/kg Test substance: Ethyl Acetate; (literature value)
Skin corrosion/irritation	(rabbit): OECD Test Guideline 404 Test substance: Ethanol Not irritating, (literature value)
	(rabbit) Test substance: Ethyl Acetate Not irritating, (literature value)
Eye damage/irritation	(rabbit): OECD Test Guideline 405 Test substance: Ethanol irritating, (literature value)
	(rabbit) Test substance: Ethyl Acetate slight irritation, (literature value)
Respiratory or skin sensitization	guinea pig: not sensitizing; Maximisation Test Ethanol, (literature value)
	guinea pig: not sensitizing; Maximisation Test Ethyl Acetate, OECD Test Guideline 406
Germ cell mutagenicity	Genotoxicity in vitro: Type: Ames test; OECD Test Guideline 471 System: Salmonella typhimurium; with and without metabolic activation



Ethanol SDA 35A 190 Proof

Result: In vitro tests did not show mutagenic effects.

Test substance: Ethanol

(literature value)

Type: Ames test

System: Salmonella typhimurium; with and without metabolic activation

Result: In vitro tests did not show mutagenic effects.

Test substance: Ethyl Acetate

(literature value)

Genotoxicity in vivo:

no data available

Assessment Mutagenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity **Reproductive toxicity:**

no data available

Assessment Reproductive toxicity:

no data available

Teratogenicity:

no data available

Assessment teratogenicity:

no data available

STOT - single exposure no data available

STOT - repeated exposure rat; Oral; 90-day;
NOAEL: 1,730 mg/kg
LOAEL: 3,160 mg/kg
Test substance: Ethanol
Based on available data, the classification criteria are not met.

Aspiration toxicity no data available

Carcinogenicity **Assessment carcinogenicity:**
Contains no ingredient listed as a carcinogen

SECTION 12 ECOLOGICAL INFORMATION

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)) 96 hours: > 100 mg/l; flow-through test
Test substance: Ethanol
(literature value)

LC50 (Pimephales promelas (fathead minnow)) 96 hours: > 100 mg/l; semi-static test
Test substance: Ethyl Acetate
(literature value)

Toxicity to aquatic invertebrates EC50 (Ceriodaphnia Dubia (water flea)) 48 hours: > 100 mg/l; static test
Test substance: Ethanol

Ethanol SDA 35A 190 Proof

(literature value)

EC50 (Daphnia magna (Water flea)) 48 hours: > 100 mg/l; static test

Test substance: Ethyl Acetate

(literature value)

Toxicity to algae EC50 (Chlorella vulgaris) 72 hours: > 100 mg/l; static test; OECD Test Guideline 201

Test substance: Ethanol

(literature value)

EC50 (Desmodesmus subspicatus (green algae)) 72 hours: > 100 mg/l; static test

Test substance: Ethyl Acetate

(literature value)

Chronic toxicity to aquatic invertebrates NOEC (Ceriodaphnia Dubia (water flea)) 10 d: 9.6 mg/l; semi-static test

Test substance: Ethanol

(literature value)

NOEC (Daphnia magna (Water flea)) 21 d: > 1 - 10 mg/l; semi-static test; OECD Test Guideline 211

Test substance: Ethyl Acetate

(literature value)

Biodegradation Readily biodegradable.

OECD Test Guideline 301B (28 d): > 60 %

Test substance: Ethanol

(literature value)

OECD Test Guideline 301B (28 d): > 60 %

Test substance: Ethyl Acetate

(literature value)

Bioaccumulation Test substance: Ethanol
No bioaccumulation is to be expected (log Pow <= 4).

Test substance: Ethyl Acetate

No bioaccumulation is to be expected (log Pow <= 4).

Mobility in soil no data available

Other adverse effects no data available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Code D001 - Ignitability (RQ 100 LB). This product has the RCRA characteristic of ignitability. Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification.



Ethanol SDA 35A 190 Proof

Disposal methods Dispose of only in accordance with local, state, and federal regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.

Empty containers. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

SECTION 14 TRANSPORT INFORMATION

DOT UN 1170, Ethanol solutions, 3, II
(RQ Ethyl Acetate) When shipped in quantities greater than 125,000 lbs, RQ must be added to the shipping description.

IATA UN 1170, Ethanol solutions, 3, II
(RQ Ethyl Acetate) When shipped in quantities greater than 125,000 lbs, RQ must be added to the shipping description.

IMDG UN 1170, Ethanol solutions, 3, II
(RQ Ethyl Acetate) When shipped in quantities greater than 125,000 lbs, RQ must be added to the shipping description.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks no data available

SECTION 15 REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

OSHA Hazards (HCS 1994)
Flammable liquid, Irritant

TSCA Inventory Listing

Components

Ethanol

Acetic acid ethyl ester

CAS-No.

64-17-5

141-78-6

SARA 302 Status

Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

CAS-No.

Weight percent

SARA 311/312 Classification

"Fire hazard", "Immediate (acute) health hazard"

SARA 313 Chemical

Components

CAS-No.

Weight percent

Ethanol SDA 35A 190 Proof

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components

Acetic acid ethyl ester

Reportable Quantity

5,000 LB

Weight percent

4 %

INTERNATIONAL REGULATIONS

WHMIS Classification

Class B, Division 2: Flammable liquid.

Class D, Division 2, Subdivision B: Toxic material.

European Union

Classification according to Regulation (EU) 1272/2008.

Flammable liquids, Category 2

Eye irritation, Category 2

Australia. Inventory of Chemical Substances (AICS)	Listed
Japan. Inventory of Existing and New Chemical Substances (ENCS)	Listed
Japan. Industrial Safety & Health Law (ISHL) Inventory	Listed
Canada. Domestic Substances List (DSL) Inventory	Listed
Canadian Non-Domestic Substance Listing (NDSL)	Not listed
European Inventory of Existing Commercial Chemical Substances (EINECS) Listing	Listed
Philippines. Inventory of Chemicals / Chemical Substances (PICCS)	Listed
Korea. Existing Chemicals Inventory (KECI)	Listed
China. Inventory of Existing Chemical Substances (IECSC)	Listed
Mexico. National Inventory of Chemical Substances (INSQ)	Listed
New Zealand. Inventory of Chemicals (NZIoC)	Listed
Switzerland. Inventory of Notified New Substances (CHINV)	Listed
Taiwan. National Existing Chemical Inventory (NECI)	Listed


Please note: The names and CAS numbers which are used for this product in the stated inventories may deviate from the information which is listed in Section 3.

STATE REGULATIONS

California Prop. 65

Components

CAS-No.



Ethanol SDA 35A 190 Proof

none

SECTION 16 OTHER INFORMATION

HAZARD RATINGS

	<u>Health</u>	<u>Flammability</u>	<u>Physical Hazard/ Instability</u>
HMIS®	2	3	0
NFPA	2	3	0

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR SASOL CHEMICALS (USA) LLC'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH SASOL CHEMICALS (USA) LLC CONSIDERS ACCURATE AND RELIABLE, SASOL CHEMICALS (USA) LLC MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.
