

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

## SECTION 1. IDENTIFICATION

Product name : Heptane

Product code : Q1352, Q9231

### Manufacturer or supplier's details

Company : **Shell Chemical LP**  
PO Box 2463  
HOUSTON TX 77252-2463  
USA

SDS Request : 1-800-240-6737

Customer Service : 1-855-697-4355

### Emergency telephone number

Chemtrec Domestic (24 hr) : 1-800-424-9300

Chemtrec International (24 hr) : 1-703-527-3887

### Recommended use of the chemical and restrictions on use

Recommended use : Industrial Solvent.

Restrictions on use : This product must not be used in applications other than the above without first seeking the advice of the supplier.

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Flammable liquids : Category 2

Aspiration hazard : Category 1

Skin irritation : Category 2

Specific target organ toxicity - single exposure : Category 3 (Narcotic effects.)

Acute aquatic toxicity : Category 2

Chronic aquatic toxicity : Category 2

### GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

H225 Highly flammable liquid and vapour.

#### HEALTH HAZARDS:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

#### ENVIRONMENTAL HAZARDS:

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

##### : **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces. -  
No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equip-  
ment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/  
face protection.

P273 Avoid release to the environment.

##### **Response:**

P370+P378 In case of fire: Use appropriate media for extinction.

P301 + P310 IF SWALLOWED: Immediately call a POISON  
CENTER or doctor/ physician.

P331 Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off  
immediately all contaminated clothing. Rinse skin with water/  
shower.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-  
tion.

P304 + P340 IF INHALED: Remove victim to fresh air and keep  
at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/ physician if you feel  
unwell.

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

##### **Storage:**

P403 + P233 Store in a well-ventilated place. Keep container  
tightly closed.

P235 Keep cool.

P405 Store locked up.

##### **Disposal:**

P501 Dispose of contents and container to appropriate waste  
site or reclaimer in accordance with local and national regula-  
tions.

#### **Other hazards which do not result in classification**

May form flammable/explosive vapour-air mixture.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Possibility of organ or organ system damage from prolonged exposure; see Chapter 11 for details. Target organ(s):

Auditory system

The classification of this material is based on OSHA HCS 2012 criteria.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Synonyms : Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

### Hazardous components

Chemical Name	Synonyms	CAS-No.	Concentration (%)
Solvent naphtha (petroleum), light aliph.	Solvent naphtha (petroleum), light aliph.	64742-89-8	<= 100

### Further information

Contains:

Chemical Name	Identification number	Concentration [%]
Heptane	142-82-5, 205-563-8	>= 25 - <= 40

## SECTION 4. FIRST-AID MEASURES

- General advice : DO NOT DELAY.  
Keep victim calm. Obtain medical treatment immediately.
- If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
- In case of eye contact : Flush eye with copious quantities of water.  
If persistent irritation occurs, obtain medical attention.
- If swallowed : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.
- Most important symptoms and effects, both acute and delayed : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

- Auditory system effects may include temporary hearing loss and/or ringing in the ears.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- Immediate medical attention, special treatment : Potential for chemical pneumonitis.  
Call a doctor or poison control center for guidance.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : Do not use water in a jet.
- Specific hazards during fire-fighting : Clear fire area of all non-emergency personnel.  
Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide.  
Unidentified organic and inorganic compounds.  
Flammable vapours may be present even at temperatures below the flash point.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Will float and can be reignited on surface water.
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Keep adjacent containers cool by spraying with water.
- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Observe all relevant local and international regulations.  
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.  
Local authorities should be advised if significant spillages cannot be contained.
- : Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.  
Do not breathe fumes, vapor.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

Do not operate electrical equipment.

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapor or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Ventilate contaminated area thoroughly.  
If contamination of site occurs remediation may require specialist advice.

Additional advice : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.  
For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Chapter 15) to the National Response Center at (800) 424-8802.  
Under Section 311 of the Clean Water Act (CWA) this material is considered an oil. As such, spills into surface waters must be reported to the National Response Center at (800) 424-8802.  
This material is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Petroleum Exclusion. Therefore, releases to the environment may not be reportable under CERCLA.

---

## SECTION 7. HANDLING AND STORAGE

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

Chapter 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Precautions for safe handling : Avoid inhaling vapour and/or mists.  
Avoid contact with skin, eyes and clothing.  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

## Storage

Conditions for safe storage, including any incompatibilities : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data : Storage Temperature:  
Ambient.

Bulk storage tanks should be diked (bunded).

Locate tanks away from heat and other sources of ignition.

Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.

Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.

Keep away from aerosols, flammables, oxidizing agents, cor-

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

rosives and from other flammable products which are not harmful or toxic to man or to the environment. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

- Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., For container paints, use epoxy paint, zinc silicate paint.  
Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.
- Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.
- Specific use(s) : Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity). CENELEC CLC/TR 50404 (Electrostatics – Code of practice for the avoidance of hazards due to static electricity).

## SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Heptane	142-82-5	TWA	85 ppm 350 mg/m <sup>3</sup>	NIOSH REL
		C	440 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0
		STEL	500 ppm 2,000 mg/m <sup>3</sup>	OSHA P0
Stoddard Solvent	8052-41-3	TWA	500 ppm 2,900 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm	ACGIH
Solvent naphtha (petroleum), light aliph.	64742-89-8	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1

### Biological occupational exposure limits

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

No biological limit allocated.

## Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods  
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods  
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances  
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany  
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

**Engineering measures** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:  
Use sealed systems as far as possible.  
Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.  
Local exhaust ventilation is recommended.  
Firewater monitors and deluge systems are recommended.  
Eye washes and showers for emergency use.  
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.  
Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

## Personal protective equipment

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health,



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapors [Type A boiling point >65°C (149°F)].

Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

## Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

## Eye protection

: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

## Skin and body protection

: Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron. Wear antistatic and flame retardant clothing, if a local risk assessment deems it so.

## Protective measures

: Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

## Hygiene measures

: Wash hands before eating, drinking, smoking and using the

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

toilet.  
Launder contaminated clothing before re-use.  
Do not ingest. If swallowed then seek immediate medical  
assistance.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid.
Colour	: colourless
Odour	: Paraffinic
Odour Threshold	: Data not available
pH	: Not applicable
Melting point/freezing point	: Data not available
Boiling point/boiling range	: 90 - 100 °C / 194 - 212 °F
Flash point	: < -7 °C / < 19 °F
Evaporation rate	: Data not available
Flammability (solid, gas)	: Extremely flammable.
Upper explosion limit	: upper flammability limit 7 %(V)
Lower explosion limit	: lower flammability limit 1 %(V)
Vapour pressure	: 6.000 - 7.700 Pa (20 °C / 68 °F)
Relative vapour density	: 3.52
Relative density	: 0.7 - 0.71 (20 °C / 68 °F)
Density	: Typical 713 kg/m <sup>3</sup> (15 °C / 59 °F) Method: ASTM D4052
Solubility(ies) Water solubility	: 2.6 mg/l immiscible (25 °C / 77 °F)
Partition coefficient: n- octanol/water	: Data not available
Auto-ignition temperature	: 246 - 260 °C / 475 - 500 °F Method: ASTM E-659

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

Decomposition temperature	: Not applicable
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: Typical 0.64 mm <sup>2</sup> /s (25 °C / 77 °F)
Explosive properties	: Not applicable
Oxidizing properties	: Data not available
Surface tension	: Data not available
Conductivity	: Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid
Molecular weight	: Data not available

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: No hazardous reaction is expected when handled and stored according to provisions. Stable under normal conditions of use.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Avoid heat, sparks, open flames and other ignition sources.  In certain circumstances product can ignite due to static electricity.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

## SECTION 11. TOXICOLOGICAL INFORMATION

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

Basis for assessment : Information given is based on product testing, and/or similar products, and/or components.

## Information on likely routes of exposure

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

## Acute toxicity

### Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Expected to be of low toxicity:

Acute inhalation toxicity : LC 50 (Rat): > 20 mg/l  
Remarks: Expected to be of low toxicity:

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Remarks: Expected to be of low toxicity:

## Skin corrosion/irritation

### Product:

Remarks: Causes skin irritation.

## Serious eye damage/eye irritation

### Product:

Remarks: Not irritating to eye.

## Respiratory or skin sensitisation

### Product:

Remarks: Not expected to be a sensitiser.

## Germ cell mutagenicity

### Product:

: Remarks: Not mutagenic.

## Carcinogenicity

### Product:

Remarks: Not expected to be carcinogenic.

## IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

## ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

## OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

## NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## Reproductive toxicity

### Product:

:

Remarks: Not a developmental toxicant., Does not impair fertility.

## STOT - single exposure

### Product:

Remarks: May cause drowsiness and dizziness., High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

## STOT - repeated exposure

### Product:

Remarks: Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss., Kidney: caused kidney effects in male rats which are not considered relevant to humans

## Aspiration toxicity

### Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## Further information

### Product:

Remarks: Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest., Classifications by other authorities under varying regulatory frameworks may exist.

---

## SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment

: Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

## Ecotoxicity

### Product:

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

- Toxicity to fish (Acute toxicity) : Remarks: Expected to be harmful:  
LL/EL/IL50 >10 <= 100 mg/l
- Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: Expected to be toxic:  
LC/EC/IC50 >1 - <=10 mg/l
- Toxicity to algae (Acute toxicity) : Remarks: Expected to be harmful:  
LL/EL/IL50 >10 <= 100 mg/l
- Toxicity to fish (Chronic toxicity) : Remarks: Data not available
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: NOEC/NOEL expected to be > 0.1 - <= 1.0 mg/l
- Toxicity to bacteria (Acute toxicity) : Remarks: Data not available

## **Persistence and degradability**

### **Product:**

- Biodegradability : Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

## **Bioaccumulative potential**

### **Product:**

- Bioaccumulation : Remarks: Has the potential to bioaccumulate.

## **Mobility in soil**

### **Product:**

- Mobility : Remarks: Floats on water.  
If it enters soil, it will adsorb to soil particles and will not be mobile.

## **Other adverse effects**

no data available

### **Product:**

- Additional ecological information : Physical properties indicate that hydrocarbon gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.

Not expected to have ozone depletion potential.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

- Waste from residues : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
- Do not dispose into the environment, in drains or in water courses  
Waste product should not be allowed to contaminate soil or water.
- Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Comply with any local recovery or waste disposal regulations.
- Local legislation  
Remarks : Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.

## SECTION 14. TRANSPORT INFORMATION

### National Regulations

#### US Department of Transportation Classification (49 CFR Parts 171-180)

- UN/ID/NA number : UN 1206  
Proper shipping name : HEPTANES  
Class : 3  
Packing group : II  
Labels : 3  
Marine pollutant : no

### International Regulation

#### IATA-DGR

- UN/ID No. : UN 1206  
Proper shipping name : HEPTANES  
Class : 3  
Packing group : II  
Labels : 3

#### IMDG-Code

- UN number : UN 1206  
Proper shipping name : HEPTANES

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

Class : 3  
Packing group : II  
Labels : 3  
Marine pollutant : yes

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : X  
Ship type : 2  
Product name : Heptane (all isomers)  
Special precautions : Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

## Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

## SECTION 15. REGULATORY INFORMATION

**OSHA Hazards** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

### Pennsylvania Right To Know

Solvent naphtha (petroleum), light aliph. 64742-89-8  
Heptane 142-82-5

### New Jersey Right To Know

Heptane 142-82-5

### California Prop 65

This product does not contain any chemicals known to State



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

of California to cause cancer, birth defects, or any other reproductive harm.

## The components of this product are reported in the following inventories:

AICS : Listed

DSL : Listed

IECSC : Listed

KECI : Listed

PICCS : Listed

EINECS : Listed

TSCA : Listed

Other regulations : The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

## SECTION 16. OTHER INFORMATION

### Further information

NFPA Rating (Health, Fire, Reactivity) 1, 3, 0

A vertical bar (|) in the left margin indicates an amendment from the previous version. Due to the conversion of this product to GHS classification and labelling, there has been a significant change to the nature of the information presented in chapter 2.

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists  
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road  
AICS = Australian Inventory of Chemical Substances  
ASTM = American Society for Testing and Materials  
BEL = Biological exposure limits  
BTEX = Benzene, Toluene, Ethylbenzene, Xylenes  
CAS = Chemical Abstracts Service  
CEFIC = European Chemical Industry Council  
CLP = Classification Packaging and Labelling  
COC = Cleveland Open-Cup  
DIN = Deutsches Institut für Normung  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
DSL = Canada Domestic Substance List  
EC = European Commission  
EC50 = Effective Concentration fifty

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 14.0

Revision Date: 03/09/2015

Print Date: 03/10/2015

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals  
ECHA = European Chemicals Agency  
EINECS = The European Inventory of Existing Commercial Chemical Substances  
EL50 = Effective Loading fifty  
ENCS = Japanese Existing and New Chemical Substances Inventory  
EWC = European Waste Code  
GHS = Globally Harmonised System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association  
IC50 = Inhibitory Concentration fifty  
IL50 = Inhibitory Level fifty  
IMDG = International Maritime Dangerous Goods  
INV = Chinese Chemicals Inventory  
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables  
KECI = Korea Existing Chemicals Inventory  
LC50 = Lethal Concentration fifty  
LD50 = Lethal Dose fifty per cent.  
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading  
LL50 = Lethal Loading fifty  
MARPOL = International Convention for the Prevention of Pollution From Ships  
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level  
OE\_HP V = Occupational Exposure - High Production Volume  
PBT = Persistent, Bioaccumulative and Toxic  
PICCS = Philippine Inventory of Chemicals and Chemical Substances  
PNEC = Predicted No Effect Concentration  
REACH = Registration Evaluation And Authorisation Of Chemicals  
RID = Regulations Relating to International Carriage of Dangerous Goods by Rail  
SKIN\_DES = Skin Designation  
STEL = Short term exposure limit  
TRA = Targeted Risk Assessment  
TSCA = US Toxic Substances Control Act  
TWA = Time-Weighted Average  
vPvB = very Persistent and very Bioaccumulative

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date : 03/09/2015

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.