

SAFETY DATA SHEET



n-Butyl acetate

10430

Version / Revision

2 .00***

Supersedes Version

1 .00***

Revision Date

30-Apr-2015

Issuing date

04-May-2015

SECTION 1: Identification

1.1. Product identifier

Identification of the substance/preparation

n-Butyl acetate

CAS-No

123-86-4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance / Preparation

solvent

1.3. Details of the supplier of the safety data sheet

Supplier

OXEA Corporation
1505 West LBJ Freeway, Suite 400
Dallas, TX 75234
USA
Phone: +1 972 481 2700

Product Information

Product Stewardship
FAX: +49 (0)208 693 2053
email: psq@oxea-chemicals.com

1.4. Emergency telephone number

Emergency telephone number

in USA, call 800 424 9300
outside USA, call 703 527 3887, collect calls accepted
available 24/7***

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This substance is classified in accordance with paragraph (d) of §1910.1200 (GHS-US classification).***

Target Organ Systemic Toxicant - Single exposure Category 3, H336***

Flammable liquid Category 3, H226***

Environmental hazard Aquatic Acute 3; H402***

OSHA Specified Hazards

Not applicable.

2.2. Label elements

Labeling according to §1910.1200 (GHS-US labeling).***

Emergency telephone number

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted

1 / 14

USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

Hazard symbol(s)



Signal word

Warning***

Hazard statements

H226: Flammable liquid and vapor.
H336: May cause drowsiness or dizziness.
H402: Harmful to aquatic life***

Precautionary statements

Prevention

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/ lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing gas/mist/vapours.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves/eye protection/face protection.***

Response

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312: Call a POISON CENTER/doctor if you feel unwell.***

Storage

P403 + P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.***

Disposal

P501: Dispose of contents/container in accordance with local regulation.***

2.3. Other hazards

Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback
Vapours may form explosive mixture with air
Components of the product may be absorbed into the body by inhalation
Repeated exposure may cause skin dryness or cracking***

SECTION 3: Composition/information on ingredients

Emergency telephone number
2 / 14

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

3.1. Substances

Component	CAS-No	Concentration (%)
n-Butyl acetate***	123-86-4	> 99,0

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Keep at rest. Aerate with fresh air. When symptoms persist or in all cases of doubt seek medical advice.

Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.

Skin

Wash off immediately with soap and plenty of water. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion

Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Main symptoms

cough, nausea, vomiting, headache, unconsciousness, shortness of breath, dizziness, narcosis.

Special hazard

Lung oedema, central nervous system effects, Prolonged skin contact may defat the skin and produce dermatitis.

4.3. Indication of any immediate medical attention and special treatment needed

General advice

Remove contaminated, soaked clothing immediately and dispose of safely. First aider needs to protect himself.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

foam, dry chemical, carbon dioxide (CO₂), water spray

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Emergency telephone number
3 / 14

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

Under conditions giving incomplete combustion, hazardous gases produced may consist of:
carbon monoxide (CO)
carbon dioxide (CO₂)
Combustion gases of organic materials must in principle be graded as inhalation poisons
Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback
Vapours may form explosive mixture with air

5.3. Advice for firefighters

Special protective equipment for firefighters

Fire fighter protection should include a self-contained breathing apparatus (NIOSH-approved or EN 133) and full fire-fighting turn out gear.

Precautions for firefighting

Cool containers / tanks with water spray. Dike and collect water used to fight fire. Water run-off can cause environmental damage. Keep people away from and upwind of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep people away from and upwind of spill/leak. Ensure adequate ventilation, especially in confined areas. Keep away from heat and sources of ignition. For emergency responders: Personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage. Do not discharge product into the aquatic environment without pretreatment (biological treatment plant).

6.3. Methods and material for containment and cleaning up

Methods for containment

Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.

Methods for cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. If liquid has been spilt in large quantities clean up promptly by scoop or vacuum. Dispose of in accordance with local regulations. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

6.4. Reference to other sections

For personal protective equipment see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

Advice on safe handling

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms.

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Advice on the protection of the environment

See Section 8: Environmental exposure controls.

Incompatible products

strong acids and strong bases
strong oxidizing agents

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). In case of fire, emergency cooling with water spray should be available. Ground and bond containers when transferring material. Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback. Vapours may form explosive mixture with air.

Technical measures/Storage conditions

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care.

Suitable material

stainless steel, mild steel, aluminium

Unsuitable material

copper, Attacks some forms of plastic and rubber

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits United States of America

US ACGIH

Component	TWA (mg/m ³)	TWA (ppm)	STEL (mg/m ³)	STEL (ppm)
n-Butyl acetate*** CAS: 123-86-4		150 ***		200***

US OSHA Z-1

Component	Ceiling (mg/m ³)	Ceiling (ppm)	PEL (mg/m ³)	PEL (ppm)	Skin Designation
n-Butyl acetate*** CAS: 123-86-4			710***	150***	

Emergency telephone number
5 / 14

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

Note

For details and further information please refer to the original regulation.

8.2. Exposure controls

Appropriate Engineering controls

General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.

Individual protection measures, such as personal protective equipment

General industrial hygiene practice

Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Ensure that eyewash stations and safety showers are close to the workstation location.

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Eye protection

Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.

Hand protection

Wear protective gloves. Recommendations are listed below. Other protective material may be used, depending on the situation, if adequate degradation and permeation data is available. If other chemicals are used in conjunction with this chemical, material selection should be based on protection for all chemicals present.

Suitable material	butyl-rubber
Evaluation	according to EN 374: level 3
Glove thickness	approx 0,3 mm
Break through time	approx 60 min

Suitable material	polyvinylchloride / nitrile rubber
Evaluation	according to EN 374: level 2
Glove thickness	approx 0,9 mm
Break through time	approx 30 min

Skin and body protection

Impervious clothing. Wear face-shield and protective suit for abnormal processing problems.

Respiratory protection

Respirator with filter for organic vapour. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Equipment should conform to NIOSH.

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

Environmental exposure controls

If possible use in closed systems. If leakage can not be prevented, the substance needs to be suck off at the emersion point, if possible without danger. Observe the exposure limits, clean exhaust air if needed. If recycling is not practicable, dispose of in compliance with local regulations. Inform the responsible authorities in case of leakage into the atmosphere, or of entry into waterways, soil or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid				
Colour	colourless				
Odour	fruity				
Odour threshold	7 - 20 ppm				
pH	6,2 (5 g/l in water @ 20 °C (68 °F))				
Melting point/range	< -130 °F (< -90 °C) (Pour point)				
Boiling point/range	259 °F (126 °C) @ 1 atm (101,3 kPa)				
Flash point	81 °F (27 °C)				
Method	EU A.9				
Evaporation rate	1,0 (n-Butyl acetate = 1)				
Flammability (solid, gas)	Does not apply, the substance is a liquid				
Lower explosion limit	1,2 Vol %				
Upper explosion limit	7,5 Vol %				
Vapour pressure	***				
Values	Values	Values	@ °C	@ °F	Method
[hPa]	[kPa]	[atm]			
15	1,5***	0,015***	20	68	
63	6,3***	0,062***	50	122	
Vapour density	4,0 (Air = 1) @ 20 °C (68 °F)				
Relative density	***				
Values	@ °C	@ °F	Method		
0,881	20	68	DIN 51757		
Solubility	No data available				
Water solubility	5,3 g/l @ 68 °F (20 °C) OECD 105				
log Pow	2,3 (measured) OECD 117				
Autoignition temperature	779 °F (415 °C)				
Method	DIN 51794				
Decomposition temperature	No data available				
Viscosity	0,73 mPa*s @ 68 °F (20 °C)				
Method	dynamic, ASTM D445				

9.2. Other information

Molecular weight	116,16
Molecular formula	C6 H12 O2
Oxidizing properties	Does not apply, substance is not oxidising. There are no chemical groups associated with oxidizing properties
Refractive Index	1,393 @ 68 °F (20 °C)

Emergency telephone number
7 / 14

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

Explosive properties Does not apply, substance is not explosive. There are no chemical groups associated with explosive properties
Surface tension 61,3 mN/m (1 g/l @ 20°C), OECD 115

SECTION 10: Stability and reactivity

10.1. Reactivity

The reactivity of the product corresponds to the typical reactivity shown by the substance group as described in any text book on organic chemistry.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Avoid contact with heat, sparks, open flame and static discharge. Avoid any source of ignition.

10.5. Incompatible materials

strong acids and strong bases, strong oxidizing agents.

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure Ingestion, Inhalation, Eye contact, Skin contact***

n-Butyl acetate*, CAS: 123-86-4**

Main symptoms

dizziness, narcosis, cough, nausea, vomiting, headache, unconsciousness, shortness of breath.

Target Organ Systemic Toxicant - Single exposure

The available data lead to the classification given in section 2***

Target Organ Systemic Toxicant - Repeated exposure

Repeated exposure may cause skin dryness or cracking

Based on available data, the classification criteria are not met for:

STOT RE***

Acute toxicity

n-Butyl acetate (123-86-4)

Emergency telephone number
8 / 14

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

Routes of Exposure	Endpoint	Values	Species	Method
Oral	LD50	10760 mg/kg	rat, male/female	OECD 423
Dermal	LD50	> 14112 mg/kg	rabbit	OECD 402
Inhalative	LC0	23,4 mg/l (4h)	rat, male/female	OECD 403, in vivo, aerosol

n-Butyl acetate*, CAS: 123-86-4**

Assessment

Based on available data, the classification criteria are not met for:

Acute oral toxicity
Acute dermal toxicity
Acute inhalation toxicity***

Irritation and corrosion				
n-Butyl acetate (123-86-4)				
Target Organ Effects	Species	Result	Method	
Skin	rabbit	No skin irritation	OECD 404	
Eyes	rabbit	No eye irritation	OECD 405	

n-Butyl acetate*, CAS: 123-86-4**

Assessment

Based on available data, the classification criteria are not met for:

skin irritation/corrosion
eye irritation/corrosion
For respiratory irritation, no data are available***

Sensitization				
n-Butyl acetate (123-86-4)				
Target Organ Effects	Species	Evaluation	Method	
Skin	mouse	not sensitizing	MEST	
Skin	guinea pig	not sensitizing	Maximisation Test	
Skin	guinea pig	not sensitizing	OECD 406	

n-Butyl acetate*, CAS: 123-86-4**

Assessment

Based on available data, the classification criteria are not met for:

Skin sensitization
For respiratory sensitization, no data are available***

Subacute, subchronic and prolonged toxicity				
n-Butyl acetate (123-86-4)				
Type	Dose	Species	Method	
90-day	NOAEC: 500 ppm	rat, male/female	EPA OTS 798.2450	Inhalation

n-Butyl acetate*, CAS: 123-86-4**

Assessment

Based on available data, the classification criteria are not met for:

STOT RE***

Emergency telephone number
9 / 14

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

Carcinogenicity, Mutagenicity, Reproductive toxicity					
n-Butyl acetate (123-86-4)					
Type	Dose	Species	Evaluation	Method	
Mutagenicity		Salmonella typhimurium	negative	OECD 471 (Ames)	
Mutagenicity		CHL	negative (without metabolic activation)	OECD 473 (Chromosomal Aberration)	
Reproductive toxicity	NOAEC: 3615 mg/m ³	rat, male/female		OECD 416	
Reproductive toxicity	LOAEC: 7230 mg/m ³	rat		OECD 414	Developmental toxicity

n-Butyl acetate*, CAS: 123-86-4**

CMR Classification

The available data on CMR properties are summarized in the table above. They do not indicate a classification into categories 1A or 1B***

Evaluation

In vitro tests did not show mutagenic effects***

n-Butyl acetate*, CAS: 123-86-4**

Other adverse effects

Components of the product may be absorbed into the body by inhalation.

Note

Handle in accordance with good industrial hygiene and safety practice. Further details on substance data can be found in the registration dossier under the following link: <http://apps.echa.europa.eu/registered/registered-sub.aspx>.

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity			
n-Butyl acetate (123-86-4)			
Species	Exposure time	Dose	Method
Daphnia magna (Water flea)	48h	EC50: 44 mg/l	
Pimephales promelas (fathead minnow)	96h	LC50: 18 mg/l	OECD 203
Desmodesmus subspicatus	72h	EC50: 647,7 mg/l	Growth rate
Desmodesmus subspicatus	72h	NOEC: 200 mg/l	Growth rate
Tetrahymena pyriformis	40 h	IC50: 356 mg/l	

12.2. Persistence and degradability

n-Butyl acetate*, CAS: 123-86-4**

Biodegradation

83 % (28 d), aerobic, Readily biodegradable, OECD 301 D.

Emergency telephone number
10 / 14

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

12.3. Bioaccumulative potential

log Pow 2,3 (measured) OECD 117

12.4. Mobility in soil

Surface tension 61,3 mN/m (1 g/l @ 20°C) OECD 115

12.5 Other adverse effects

n-Butyl acetate***, CAS: 123-86-4

No data available***

Note

Avoid release to the environment.

SECTION 13: Disposal considerations

Product Information

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.

Uncleaned empty packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

D.O.T. (49CFR)

14.1. UN number	*** UN 1123
14.2. UN proper shipping name	*** Butyl acetates
14.3. Transport hazard class(es)	*** 3
14.4. Packing group	*** III
14.5. Environmental hazards	no***
14.6. Special precautions for user	***
Reportable Quantity (RQ)	5000 lb/ 2270 kg (Butyl acetate)
Emergency Response Guide	129

ICAO/IATA

14.1. UN number	*** UN 1123
14.2. UN proper shipping name	*** Butyl acetates***

Emergency telephone number
11 / 14

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

14.3. Transport hazard class(es) *** 3
14.4. Packing group *** III
14.5. Environmental hazards no***
14.6. Special precautions for user no data available***

IMDG

14.1. UN number *** UN 1123
14.2. UN proper shipping name *** Butyl acetates***
14.3. Transport hazard class(es) *** 3
14.4. Packing group *** III
14.5. Environmental hazards no***
14.6. Special precautions for user ***
EmS F-E, S-D

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Product name Butyl acetate
Ship type 3
Pollution category Y

SECTION 15: Regulatory information

Federal and State Regulations

Components of the product are listed in the quoted regulations. For details please refer to the regulations directly. This list is not exhaustive, please check for other applicable regulations.

Federal Regulations

This product is listed on the TSCA inventory

n-Butyl acetate***, CAS: 123-86-4

CERCLA Hazardous Substance***

CERCLA RQ 5000 LBS***

State Regulations

n-Butyl acetate***, CAS: 123-86-4

CA Hazardous Substances (Director's) List***

IL Chemical Safety Act***

MA Hazardous Substances List***

MA RTK List***

MN Hazardous Substances List***

NY RTK List***

PA RTK List***

RI RTK List***

Emergency telephone number
12 / 14

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

International Inventories

n-Butyl acetate*, CAS: 123-86-4**

AICS (AU)***
DSL (CA)***
IECSC (CN)***
EC-No. 2046581 (EU)***
ENCS (2)-731 (JP)***
ISHL (2)-731 (JP)
ISHL 2-(6)-226 (JP)***
KECI KE-04179 (KR)***
INSQ (MX)***
PICCS (PH)***
TSCA (US)***
NZIoC (NZ)***
TCSI (TW)***

SECTION 16: Other information

Revision Date 30-Apr-2015
Issuing date 04-May-2015

Hazard Rating Systems

NFPA (National Fire Protection Association)

Health Hazard	2
Fire Hazard	3
Reactivity	0

HMIS (Hazardous Material Information System)

Health Hazard	2
Flammability	3
Physical Hazard	0

Training advice

For effective first-aid, special training / education is needed.

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on Oxea owned data and public sources deemed valid or acceptable. The absence of data elements required by ANSI or Annex II, Regulation 1907/2006/EC indicates, that no data meeting these requirements is available.

Further information for the safety data sheet

Changes against the previous version are marked by ***. Observe national and local legal requirements. For more information, other material safety data sheets or technical data sheets please consult the Oxea homepage (www.oxea-chemicals.com).

Emergency telephone number
13 / 14

in USA, call 800 424 9300; outside USA, call USA 703 527 3887, collect calls accepted
USA (A-US)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 2 .00***

Disclaimer

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. Oxea makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

End of Safety Data Sheet